



FAA Approved Facility

Passive L1/L2 GPS Antenna, P/N: 1.9G1215X-XRS-4

Low Profile 1.9" Square, Flat/Back Mount Configuration

Suitable for Forming Multiple Element CRPA

"-PL-" or "-AL-" for Limiter Options for High Power Pulse Protection



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . http://www.antcom.com

Wide Band GNSS Option Is Available

SPECIFICATION S

ZONE	REV	DESCRIPTION	REVISIONS			
			DATE	APPROVED		

ELECTRICAL:

	L1: (1575.42±12) MHz			L2: (1227.60±12) MHz		
FREQUENCY:						
RADIATION PATTERN:	HEMISPHERICAL					
POLARIZATION:	RHCP					
VSWR:	< 1.5:1			< 1.5:1		
IMPEDANCE:	50 ohms			50 ohms		
ANTENNA GAIN (dBi):	Free Space	3 in G.P.	4 ft G.P.	Free Space	3 in G.P.	4 ft G.P.
@ 90° (ZENITH):	+2.7	+4.7	+3.1	+1.5	+3.3	+4.5
@ 10° Elevation:	-4.4	-1.8	-1.9	-6.7	-3.8	-3.5
@ 20° Elevation:	-2.3	-0.3	+0.6	-5.6	-2.0	-0.8
@ 30° Elevation:	-0.8	+1.4	+1.7	-4.5	-0.5	+1.4
@ 60 - 90° Elevation:	>2.0	>3.9	>2.4	> 0.0	>2.7	>2.2
BEAM WIDTH (3dB):	113 Deg.	114 Deg.	143 Deg.	85 Deg.	106 Deg.	74 Deg.
AXIAL RATIO:	2 dB			2 dB		
LIGHTNING PROTECTION:	DC GROUNDING					

LNA OPTION:

LNA GAIN: (21.0+/-2.0) dB
 LNA NOISE FIGURE: 1.8 dB
 LNA P 1dB Out: +16 dBm
 VOLTAGE/CURRENT: (+2.8 TO +28) Volts DC / (15 TO 25) mA

MECHANICAL:

SIZE: 1.912in.[48.56mm]SQ.
 HEIGHT: 0.36 in. [9.02 mm]
 WEIGHT: 2.0 oz. (56.7g)
 FINISH: SKYDROLRESISTANTPOLYURETHANENAMEL
 BASE IRIDITEPER MIL-C-5441

MATERIAL: 6061-T6ALUMINUMALLOY BASE
 THERMOSETPLASTICRADOME,UV, ABRASIONAND
 SKYDROL RESISTANCE

CONNECTOR: 0.030" DIA. PIN, 0.100" LONG
 (OPTION: SMA, TNC, TNC-Bulkhead, N, N-Bulkhead, MCX, MMCX, or Cable)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]
 ALTITUDE: 70,000ft.
 VIBRATION: >30 G's
 LEAKAGE: HERMETICALLYSEAL

FEDERAL & MILITARY SPECIFICATIONS

DESIGN TO: FAA TSO-C144, DO-160D, DO-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A AND MIL-STD-810

1	ADHESIVE GASKET	12345G-3M-1G	-	-	-	1
	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	ITEM NO
QUANTITY REQD	PARTS LIST					

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES
 TOLERANCES ARE:
 FRACTIONS DECIMALS ANGLES
 ± 1/64 .XXX ± 1°

TOLERANCE SYM PER ANSI Y14.5
 REMOVE ALL BURRS
 BREAK EXTERNAL EDGES .005 TO .015
 FILETS R .005 TO R .030
 SCREW THREADS PER MIL-S-8879
 DIA'S ON A COMMON & 2ND.005

MACHINED SURFACES ✓

DO NOT SCALE DRAWING

ANTCOM CORP. TORRANCE CALIFORNIA

1.9" SQUARE, L1/L2 PASSIVE GPS ANTENNA

DRAWN: []
 CHECKED: []
 ENGINEER: []
 APPROVED: S. HUYNH Sep-19-01
 CAD FILE NO: []

SIZE: CASE NO: D13CVE1
 DRAWING NO: 1.9G1215P-XRS-4
 REV: A

SCALE: 1/1
 SHEET 1 OF 1

P/N: 1.9G1215P-XRS-4

SIZE:	FREQ. BAND:	LNA:
1: 2" SQ.	1215, L1/L2	A2: WITH 20 dB LNA
1.9: 1.9" SQ.	15: L1 ONLY	A4: WITH 40 dB LNA
2: 2.6" DIA.		P: WITHOUT LNA
3: 3.5" DIA.		P2: WITHOUT LNA, WITH RHCP/LHCP POLARIZATION
4: MINI ARINC		P2L: WITHOUT LNA, WITH DUAL LINEAR POLARIZATION

CABLE LENGTH:	CONNECTOR:	COLOR:
X: NO CABLE	S: SMA, P: P2 PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
M: MAG. N: NO MAG	M: MCX, MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
R: CABLE LENGTH (IN)	N: NB: RS: R-SMA	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
R: RIGHT ANGLE CON.	T: TB: TNC, TNC-Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B

2. ADHESIVE GASKET IS SUPPLIED BY ANTCOM CORPORATION
 1. DIMENSIONS ARE IN MILLIMETERS [mm]

Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>
 Amplifiers/Power Divider/Combiner/Filter: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts1.pdf>