




Passive L1/L2 GPS Antenna, P/N: 2CG1215P-XS-X-5.75R-871C

For High Speed Vehicle. Compliance with Document No: 735DD0164

2.20in. Dia., 5.75in Conformal Radius without Flange Configuration, 871 °C

2 of This Antenna (Top/Bottom) Can Be Used with 2-Way Power Divider (P/N: 2G1215S-XS2-2) for Wrap Around Coverage

Other Conformal Radius, Frequencies, Connector, Color, Cable Length and Mounting Options are Available



ISO 9001:2008/FAA Approved Facility Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, #602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS		SPECIFICATIONS																																																	
THIS DOCUMENT CONTAINS CONFIDENTIAL, TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONTINGENT UPON YOUR AGREEMENT THAT YOU WILL BE LIMITED TO USE WITHIN YOUR COMPANY ONLY AND DOES NOT INCLUDE MANUFACTURE OR PROCESSING THEREOF. ANY OTHER USE IS EXPRESSLY PROHIBITED WITHOUT THE WRITTEN CONSENT OF ANTCOM CORP.		REVISIONS																																																	
		ZONE	REV																																																
		DESCRIPTION	DATE																																																
		APPROVED																																																	
		ELECTRICAL: <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>FREQUENCY:</td> <td>L1: (1575.42 ±13) MHz</td> <td>L2: (1227.60 ±13) MHz</td> </tr> <tr> <td>RADIATION PATTERN:</td> <td colspan="2">HEMISPHERICAL (360° In Azimuth/ >90° In EI)</td> </tr> <tr> <td>POLARIZATION:</td> <td>RHCP</td> <td>RHCP</td> </tr> <tr> <td>VSWR:</td> <td>< 1.5:1</td> <td>< 1.5:1</td> </tr> <tr> <td>IMPEDANCE:</td> <td>50 ohms</td> <td>50 ohms</td> </tr> <tr> <td>ANTENNA GAIN (dBi):</td> <td>Free Space</td> <td>Free Space</td> </tr> <tr> <td>@ 90 ° (ZENITH):</td> <td>+ 2.0</td> <td>+ 0.2</td> </tr> <tr> <td>@ 10 ° Elevation:</td> <td>- 5.8</td> <td>- 5.0</td> </tr> <tr> <td>@ 20 ° Elevation:</td> <td>- 4.5</td> <td>- 3.9</td> </tr> <tr> <td>@ 30 ° Elevation:</td> <td>- 2.8</td> <td>- 3.5</td> </tr> <tr> <td>@ 60 - 90 ° Elevation:</td> <td>> +1.7</td> <td>> -0.8</td> </tr> <tr> <td>BEAM WIDTH (3dB):</td> <td>105 Deg.</td> <td>90 Deg.</td> </tr> <tr> <td>AXIAL RATIO:</td> <td>3 dB</td> <td>3 dB</td> </tr> <tr> <td>LIGHTNING PROTECTION:</td> <td colspan="2">DC GROUNDING</td> </tr> <tr> <td>POWER HANDLING:</td> <td colspan="2">200 Watt CW</td> </tr> </table>		FREQUENCY:	L1: (1575.42 ±13) MHz	L2: (1227.60 ±13) MHz	RADIATION PATTERN:	HEMISPHERICAL (360° In Azimuth/ >90° In EI)		POLARIZATION:	RHCP	RHCP	VSWR:	< 1.5:1	< 1.5:1	IMPEDANCE:	50 ohms	50 ohms	ANTENNA GAIN (dBi):	Free Space	Free Space	@ 90 ° (ZENITH):	+ 2.0	+ 0.2	@ 10 ° Elevation:	- 5.8	- 5.0	@ 20 ° Elevation:	- 4.5	- 3.9	@ 30 ° Elevation:	- 2.8	- 3.5	@ 60 - 90 ° Elevation:	> +1.7	> -0.8	BEAM WIDTH (3dB):	105 Deg.	90 Deg.	AXIAL RATIO:	3 dB	3 dB	LIGHTNING PROTECTION:	DC GROUNDING		POWER HANDLING:	200 Watt CW				
FREQUENCY:	L1: (1575.42 ±13) MHz			L2: (1227.60 ±13) MHz																																															
RADIATION PATTERN:	HEMISPHERICAL (360° In Azimuth/ >90° In EI)																																																		
POLARIZATION:	RHCP	RHCP																																																	
VSWR:	< 1.5:1	< 1.5:1																																																	
IMPEDANCE:	50 ohms	50 ohms																																																	
ANTENNA GAIN (dBi):	Free Space	Free Space																																																	
@ 90 ° (ZENITH):	+ 2.0	+ 0.2																																																	
@ 10 ° Elevation:	- 5.8	- 5.0																																																	
@ 20 ° Elevation:	- 4.5	- 3.9																																																	
@ 30 ° Elevation:	- 2.8	- 3.5																																																	
@ 60 - 90 ° Elevation:	> +1.7	> -0.8																																																	
BEAM WIDTH (3dB):	105 Deg.	90 Deg.																																																	
AXIAL RATIO:	3 dB	3 dB																																																	
LIGHTNING PROTECTION:	DC GROUNDING																																																		
POWER HANDLING:	200 Watt CW																																																		
<p>P/N: 2CG1215P-XS-X-5.75R-871C</p> <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>SIZE:</td> <td>FREQ. BAND:</td> <td>LNA:</td> </tr> <tr> <td>1: 2" SQ.</td> <td>1215: L1/L2</td> <td>A: WITH LNA</td> </tr> <tr> <td>1.9: 1.9" SQ.</td> <td>15: L1 ONLY</td> <td>P: WITHOUT LNA</td> </tr> <tr> <td>3: 3.5" SQ.</td> <td></td> <td>AL: WITH LNA/LIMITER/FILTER (INPUT: +50dBm, OUPUT:-30 dBm)</td> </tr> <tr> <td>2: 2.6" DIA.</td> <td></td> <td>PL: PASSIVE WITH LIMITER/FILTER (INPUT: +50dBm, OUPUT:+30 dBm)</td> </tr> <tr> <td>4: MINI ARINC</td> <td></td> <td></td> </tr> </table>		SIZE:	FREQ. BAND:	LNA:	1: 2" SQ.	1215: L1/L2	A: WITH LNA	1.9: 1.9" SQ.	15: L1 ONLY	P: WITHOUT LNA	3: 3.5" SQ.		AL: WITH LNA/LIMITER/FILTER (INPUT: +50dBm, OUPUT:-30 dBm)	2: 2.6" DIA.		PL: PASSIVE WITH LIMITER/FILTER (INPUT: +50dBm, OUPUT:+30 dBm)	4: MINI ARINC			MECHANICAL: SIZE: 2.191 In [55.65 mm] DIAMETER HEIGHT = 0.492In. [12.50 mm] WEIGHT: <3.0 oz. (85 g) FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL BASE IRIDITE PER MIL-C-5441F COATING PER MIL-PRF-85582E AND MIL-PRF-85285E MATERIAL: 316H STAINLESS STEEL HOUSING CERAMIC RADOME, ABRASION, UV, SOLVENT, SKYDROL RESISTANCE AND FIRE RETARDANT CONNECTOR: SMA FEMALE (OPTION: TNC, TNC Bulkhead, N, N Bulkhead, MCX, or MMCX) ENVIRONMENTAL: TEMPERATURE: -70 °F TO +1600 °F [-57 °C TO +871 °C] ALTITUDE: 100,000 ft. SHOCK/VIBRATION: 100 G's LEAKAGE: HERMETICALLY SEAL FEDERAL & MILITARY SPECIFICATIONS: DESIGN TO: FAA TSO-C144, DO-160D (ENV/EMI), DO-228 (ENV/EMI), MIL-C-5541F, MIL-PRF-39012 (CONN), MIL-STD-810G (ENV/EMI), MIL-HDBK-5400 (ELEC) MIL-STD-464C (ELEC MAG), MIL-STD-130N-1 (ID), MIL-STD-889B (METAL) RCC-319-14 (TERMINATION) , RCC-324-01(SAFETY), MIL-STD-1472 MIL-E-5400, MIL-I-45208A, SAE J1455, AND NAS411-1 (HAZ) ACCEPTANCE TEST PROCEDURE: ATP-GPS-L1L2-100																															
SIZE:	FREQ. BAND:	LNA:																																																	
1: 2" SQ.	1215: L1/L2	A: WITH LNA																																																	
1.9: 1.9" SQ.	15: L1 ONLY	P: WITHOUT LNA																																																	
3: 3.5" SQ.		AL: WITH LNA/LIMITER/FILTER (INPUT: +50dBm, OUPUT:-30 dBm)																																																	
2: 2.6" DIA.		PL: PASSIVE WITH LIMITER/FILTER (INPUT: +50dBm, OUPUT:+30 dBm)																																																	
4: MINI ARINC																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>CABLE'S LENGTH:</td> <td>CONNECTOR:</td> <td>COLOR:</td> <td>CONFORMAL RADIUS:</td> </tr> <tr> <td>X: NO CABLE</td> <td>S: SMA; P: PINS</td> <td>-1: GLOSS WHITE #17925 PER FED-STD-595B</td> <td>5.75; 5.75in.</td> </tr> <tr> <td>M: MAG., N: NO MAG.</td> <td>M: MCX; MM: MMCX</td> <td>-2: LUSTERLESS GRAY #36320 PER FED-STD-595B</td> <td></td> </tr> <tr> <td>#: CABLE LENGTH (IN)</td> <td>SMP: SMP; SSMCR: SSMC-R</td> <td>-3: CAMO GREEN #34094 PER FED-STD-595B</td> <td></td> </tr> <tr> <td>R: RIGHT ANGLE CON.</td> <td>T, TB: TNC, TNC-Bulkhead</td> <td>-4: LUSTERLESS BLACK #37038 PER FED-STD-595B</td> <td></td> </tr> <tr> <td></td> <td></td> <td>-5: DESERT TAN #33446 PER FED-STD-595B</td> <td></td> </tr> </table>		CABLE'S LENGTH:	CONNECTOR:	COLOR:	CONFORMAL RADIUS:	X: NO CABLE	S: SMA; P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B	5.75; 5.75in.	M: MAG., N: NO MAG.	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B		#: CABLE LENGTH (IN)	SMP: SMP; SSMCR: SSMC-R	-3: CAMO GREEN #34094 PER FED-STD-595B		R: RIGHT ANGLE CON.	T, TB: TNC, TNC-Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B				-5: DESERT TAN #33446 PER FED-STD-595B		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>QUANTITY REQD</td> <td>DESCRIPTION</td> <td>PART NO</td> <td>MATERIAL</td> <td>FINISH</td> <td>ITEM NO</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>3</td> </tr> <tr> <td>1</td> <td>2-WAYS POWER DIVIDER</td> <td>2G1215S-XS2-2</td> <td></td> <td></td> <td>2</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td>1</td> </tr> </table>		QUANTITY REQD	DESCRIPTION	PART NO	MATERIAL	FINISH	ITEM NO						3	1	2-WAYS POWER DIVIDER	2G1215S-XS2-2			2	2					1
CABLE'S LENGTH:	CONNECTOR:	COLOR:	CONFORMAL RADIUS:																																																
X: NO CABLE	S: SMA; P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B	5.75; 5.75in.																																																
M: MAG., N: NO MAG.	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B																																																	
#: CABLE LENGTH (IN)	SMP: SMP; SSMCR: SSMC-R	-3: CAMO GREEN #34094 PER FED-STD-595B																																																	
R: RIGHT ANGLE CON.	T, TB: TNC, TNC-Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B																																																	
		-5: DESERT TAN #33446 PER FED-STD-595B																																																	
QUANTITY REQD	DESCRIPTION	PART NO	MATERIAL	FINISH	ITEM NO																																														
					3																																														
1	2-WAYS POWER DIVIDER	2G1215S-XS2-2			2																																														
2					1																																														
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</td> <td>ORIGINALLY DRAWN</td> <td>S. HUYNH</td> <td>Dec-21-15</td> </tr> <tr> <td>FRACTIONS DECIMALS ANGLES</td> <td>ORIGINALLY DESIGNED</td> <td>S. HUYNH</td> <td>Dec-21-15</td> </tr> <tr> <td>± 1/64 ± .005 ± .01</td> <td>UPDATED</td> <td>S. HUYNH</td> <td>Mar-03-16</td> </tr> <tr> <td>TOLERANCE 5VM PER ANSI Y14.5</td> <td>UPDATE DRAWN</td> <td>P. TRAN</td> <td>Mar-03-16</td> </tr> <tr> <td>REMOVE ALL BURRS BREAK EXTERNAL EDGES .005 TO .015 FILED .005 TO .015</td> <td>APPROVED</td> <td>S. HUYNH</td> <td>Mar-03-16</td> </tr> <tr> <td>DRY S. ON A CLEAN SURFACE</td> <td>DO NOT SCALE DRAWING</td> <td></td> <td></td> </tr> </table>		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	ORIGINALLY DRAWN	S. HUYNH	Dec-21-15	FRACTIONS DECIMALS ANGLES	ORIGINALLY DESIGNED	S. HUYNH	Dec-21-15	± 1/64 ± .005 ± .01	UPDATED	S. HUYNH	Mar-03-16	TOLERANCE 5VM PER ANSI Y14.5	UPDATE DRAWN	P. TRAN	Mar-03-16	REMOVE ALL BURRS BREAK EXTERNAL EDGES .005 TO .015 FILED .005 TO .015	APPROVED	S. HUYNH	Mar-03-16	DRY S. ON A CLEAN SURFACE	DO NOT SCALE DRAWING			<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">ANTCOM CORP. TORRANCE, CALIFORNIA</td> </tr> <tr> <td colspan="2" style="text-align: center;">CONFORMAL L1L2 GPS ANTENNA</td> </tr> <tr> <td>REV</td> <td>DATE</td> </tr> <tr> <td>D</td> <td>3CVE1</td> </tr> <tr> <td colspan="2">PART NO: 2CG1215P-XS-X-5.75R-871C</td> </tr> <tr> <td>SCALE</td> <td>1/1</td> </tr> <tr> <td>SHEET</td> <td>1 OF 1</td> </tr> </table>		ANTCOM CORP. TORRANCE, CALIFORNIA		CONFORMAL L1L2 GPS ANTENNA		REV	DATE	D	3CVE1	PART NO: 2CG1215P-XS-X-5.75R-871C		SCALE	1/1	SHEET	1 OF 1										
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	ORIGINALLY DRAWN	S. HUYNH	Dec-21-15																																																
FRACTIONS DECIMALS ANGLES	ORIGINALLY DESIGNED	S. HUYNH	Dec-21-15																																																
± 1/64 ± .005 ± .01	UPDATED	S. HUYNH	Mar-03-16																																																
TOLERANCE 5VM PER ANSI Y14.5	UPDATE DRAWN	P. TRAN	Mar-03-16																																																
REMOVE ALL BURRS BREAK EXTERNAL EDGES .005 TO .015 FILED .005 TO .015	APPROVED	S. HUYNH	Mar-03-16																																																
DRY S. ON A CLEAN SURFACE	DO NOT SCALE DRAWING																																																		
ANTCOM CORP. TORRANCE, CALIFORNIA																																																			
CONFORMAL L1L2 GPS ANTENNA																																																			
REV	DATE																																																		
D	3CVE1																																																		
PART NO: 2CG1215P-XS-X-5.75R-871C																																																			
SCALE	1/1																																																		
SHEET	1 OF 1																																																		