




L1/L2/L5 GPS & Inmarsat/Iridium+L1/L2 Glonass Antennas, P/N: 3DG5A-XTM-X
 L1/L2 GPS Antenna P/N: 3DG1215X-XTM-X, L1/L2 GPS/Glonass Antenna P/N: 3DG1216X-XTM-X
 Rx Only Thuraya Antenna, P/N: 3DRxTA-XTM-X, Rx Only Inmarsat/Iridium Antenna, P/N: 3DRxINA-XTM-X
 Passive Rx/Tx Thuraya Antenna, P/N: 3DRxTxTP-XTM-X, Passive Rx/Tx Inmarsat/Iridium Antenna, P/N: 3DRxTxINP-XTM-X
 ISO 9001:2008/FAA Approved Facility Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>



ANTCOM CORPORATION . 367 Van Ness Way, #602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS
 THIS DOCUMENT CONTAINS CONFIDENTIAL, TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. REPRODUCTION OF THIS DATA TO ANY OTHER PARTY WITHOUT THE WRITTEN CONSENT OF ANTCOM CORP. IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

REVISIONS

ZONE	REV	DESCRIPTION	DATE	APPROVED

ELECTRICAL:

FREQUENCY (MHz):	(1575.42 ±13)	(1542.50 ±17.5)	(1642.50 ±17.5)	(1602-1616)	(1616-1626)	(1227.60 ±13)	(1252.50 ±7.5) / (1176.45 ±12)
GAIN (dBic)	L1 GPS	Rx INMARSAT	Tx INMARSAT	GLONASS	IRIDIUM	L2 GPS	L2 GLONASS/ L5 GPS
@ 90° (Zenith):	+2.9	+0.7	-1.6	+0.3	-1.2	0.0	-1.0
@ 10° Elevation:	-0.4	-2.8	-4.9	-3.1	-4.3	-2.4 to -6.3	-3.4 to -7.3
@ 20° Elevation:	+0.5	-1.7	-3.5	-1.7	-3.0	-1.8 to -4.8	-2.8 to -5.8
@ 30° Elevation:	+1.7	-0.7	-2.4	-0.7	-1.9	-1.3 to -3.4	-2.3 to -4.4
@ 45° Elevation:	+2.4	+0.2	-2.3	-0.1	-1.8	-0.5 to -1.5	-1.5 to -2.5
@ 70° Elevation:	+2.3	+0.6	-2.1	+0.2	-1.6	0.0 to -0.5	-1.0 to -1.5
BEAM WIDTH (3dB)	142 Deg.	140 Deg.	146 Deg.	144 Deg.	145 Deg.	(120 to 165) Deg.	(120 to 165) Deg.
AXIAL RATIO (dB)	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 5	1 to 5
RADIATION PATTERN:	HEMISPHERICAL						
POLARIZATION:	RHCP						
VSWR:	< 1.5:1						

SPECIFICATIONS

DC GROUNDING: YES (LIGHTNING PROTECTION)

LNA OPTION:

LNA GAIN: (22.0+/-2.0) dB
 LNA NOISE FIGURE: 2.8 dB (Filter loss is Included)
 LNA P 1dB Out: +13 dBm
 VOLTAGE/CURRENT: (+2.4 TO +5) Volts DC / (15 TO 30) mA
 REJECTION: 2 2-POLE FILTERS FOR EACH BAND

MECHANICAL:

SIZE: DIAMETER: 1.00 in. [25.40 mm]
 HEIGHT: 4.2 in. [106.68 mm]

WEIGHT: 1.715 oz (48.62 g)

FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL
 BASE IRIDITE PER MIL-C-5441

COLOR: WHITE #17925 PER FED-STD-595B

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE
 COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT, SKYDROL RESISTANCE, AND FIRE RETARDANT

CONNECTOR: TNC MALE
 (OPTION: MCX, SMA, TNC Bulkhead, N, N Bulkhead, MCX, MMCX, QMA, or Cable)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]
 ALTITUDE: 70,000 ft.
 VIBRATION: > 30 G's
 LEAKAGE: HERMETICALLY SEALED

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

ACCEPTANCE TEST PROCEDURE: ATP-GPS-L1L2-100

P/N: 3DG5A-XTM-1

FREQ. BAND:	LNA:
1215: L1/L2	A: WITH LNA
15: L1 ONLY	P: WITHOUT LNA
1216: L1/L2/INMARSAT/GLONASS/IRIDIUM	
5: L1/L2/GPS/GLONASS/INMARSAT/IRIDIUM	

QUANTITY REQD	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	TRU NO
1	1					1
-2	-1					

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES
 FRACTIONS: DECIMALS: ANGLES
 ± 1/64 .XXX .005 ± 1°
 TOLERANCE 5M PER ANSI Y14.5
 REMOVE ALL BURRS
 BREAK EXTERNAL EDGES .005 TO .015
 FILED R .005 TO R .008
 SQUARE THE ADS PER MIL-S-8879
 DIM'S ON A COMMON & 22° .005
 MACHINED SURFACES V
 DO NOT SCALE DRAWING

CABLE'S LENGTH:	CONNECTOR:	COLOR:
X: NO CABLE	S: SMA; P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
M: MAG. N: NO MAG.	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
#: CABLE LENGTH (IN)	N, NB: N, N-Bulkhead	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
R: RIGHT ANGLE CON. T, TB: TNC, TNC-Bulkhead		-4: LUSTERLESS BLACK #37038 PER FED-STD-595B

1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]

NOTES: UNLESS OTHERWISE SPECIFIED:

ANTCOM CORP. TORRANCE, CALIFORNIA

HANDHELD L1/L2 GPS/INMARSAT/GLONASS/IRIDIUM HELIX ANTENNA

DATE: 08-12-11
 DESIGNED BY: S. HUYNH
 CHECKED BY: S. HUYNH
 APPROVED BY: S. HUYNH
 CAD FILE NO: D:\3CVE1\3DG5A-XTM-1

SCALE: 1/1

SHEET 1 OF 1

ANTCOM CORP. TORRANCE, CALIFORNIA

HANDHELD L1/L2 GPS/INMARSAT/GLONASS/IRIDIUM HELIX ANTENNA

DATE: 08-12-11
 DESIGNED BY: S. HUYNH
 CHECKED BY: S. HUYNH
 APPROVED BY: S. HUYNH
 CAD FILE NO: D:\3CVE1\3DG5A-XTM-1

SCALE: 1/1

SHEET 1 OF 1

NMO Connector Option is Now Available for Some Antennas