




L1/L2/L5 GPS & Inmarsat/Iridium+L1/L2 Glonass Antennas, P/N: 6DG5A-XTM-1-PCL
 Rx Only Thuraya Antenna, P/N: 3DRxTA-XTM-1-PCL,
 Rx Only Inmarsat/Iridium Antenna, P/N: 3DRxINA-XTM-1-PCL,
 Passive Rx/Tx Thuraya Antenna, P/N: 3DRxTxTP-XTM-1-PCL,
 Passive Rx/Tx Inmarsat/Iridium Antenna, P/N: 3DRxTxINP-XTM-1-PCL,
 1" Dia. X 6.5" Tall, Swivel, Side Mount Configurations



ISO 9001:2008/FAA Approved Facility

Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS
 THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONTINGENT UPON YOUR AGREEMENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY (SAND DOES NOT INCLUDE MANUFACTURE OR REPRODUCTION). ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

ELECTRICAL: SPECIFICATIONS

FREQUENCY (MHz):	(1575.42 ±13)	(1542.50 ±17.5)	(1642.50 ±17.5)	(1602-1616)	(1616-1626)	(1227.60 ±13)	(1252.50 ±7.5)/ (1176.45 ±12)
GAIN (dBic)	L1 GPS	Rx INMARSAT	Tx INMARSAT	GLONASS	IRIDIUM	L2 GPS	L2 GLONASS/ L5 GPS
@ 90° (Zenith):	+2.9	+0.7	-1.6	+0.3	-1.2	0.0	-1.0
@ 10° Elevation:	-0.4	-2.8	-4.9	-3.1	-4.3	-2.4 to -6.3	-3.4 to -7.3
@ 20° Elevation:	+0.5	-1.7	-3.5	-1.7	-3.0	-1.8 to -4.8	-2.8 to -5.8
@ 30° Elevation:	+1.7	-0.7	-2.4	-0.7	-1.9	-1.3 to -3.4	-2.3 to -4.4
@ 45° Elevation:	+2.4	+0.2	-2.3	-0.1	-1.8	-0.5 to -1.5	-1.5 to -2.5
@ 70° Elevation:	+2.3	+0.6	-2.1	+0.2	-1.6	0.0 to -0.5	-1.0 to -1.5
BEAM WIDTH (3dB)	142 Deg.	140 Deg.	146 Deg.	144 Deg.	145 Deg.	(120 to 165) Deg.	(120 to 165) Deg.
AXIAL RATIO (dB)	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 5	1 to 5
RADIATION PATTERN:	HEMISPHERICAL						
POLARIZATION:	RHCP						
VSWR:	< 1.5:1						

Z Phase Center =
5.668 [143.97]

DC GROUNDING: YES (LIGHTNING PROTECTION)

LNA OPTION:

LNA GAIN: (22.0+/-2.0) dB
 LNA NOISE FIGURE: 2.8 dB (Filter loss is Included)
 LNA P 1dB Out: +13 dBm
 VOLTAGE/CURRENT: (+2.4 TO +5) Volts DC / (15 TO 30) mA
 REJECTION: 2 2-POLE FILTERS FOR EACH BAND

MECHANICAL:

SIZE: DIAMETER: 1.00 in. [25.40 mm]
 HEIGHT: 6.5 in. [106.68 mm]
 WEIGHT: 2.39 oz (67.76 g)
 FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL
 BASE IRIDITE PER MIL-C-5441
 COLOR: WHITE #17925 PER FED-STD-595B
 MATERIAL: 6061-T6 ALUMINUM ALLOY BASE
 COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT,
 SKYDROL RESISTANCE, AND FIRE RETARDANT
 CONNECTOR: TNC MALE
 (OPTION: MCX, SMA, TNC Bulkhead, N, N Bulkhead,
 MCX, MMCX, QMA, or Cable)

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]
 ALTITUDE: 70,000 ft.
 VIBRATION: > 30 G's
 LEAKAGE: HERMETICALLY SEALED

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541,
 MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

ACCEPTANCE TEST PROCEDURE: ATP-GPS-L1L2-100

FREQ. BAND:	LNA:	1	1						
1215: L1/L2	A: WITH LNA								1
15: L1 ONLY	P: WITHOUT LNA								
1216: L1/L2/INMARSAT/GLONASS/IRIDIUM		-2	-1	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	ITEM NO.
5: L1/L2/GPS/GLONASS/INMARSAT/IRIDIUM									

P/N: 6DG5A-XTM-1-PCL

CABLE LENGTH:	CONNECTOR:	COLOR:
X: NO CABLE	S: SMA, P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
M: MAG, N: No MAG.	M: MCX, MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
#: CABLE LENGTH (IN)	N, NB: N, N-Bulkhead	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
R: RIGHT ANGLE CON.	T, TB: TNC, TNC-Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		DECIMALS ARE ± .015		ANGLES ARE ± .1°	
FRACTIONS	DECIMALS	FRACTIONS	DECIMALS	FRACTIONS	DECIMALS
± 1/64	± .005	± 1/64	± .005	± 1/64	± .005

ANTCOM CORP. TORRANCE, CALIFORNIA

HANDHELD L1/L2/L5 GPS/INMARSAT/GLONASS/IRIDIUM HELIX ANTENNA

D3C VE 1 6DG5A-XTM-1-PCL

SCALE 1/1 SHEET 1 OF 1

NMO Connector Option is Now Available for Some Antennas