



ISO 9001:2008/FAA Approved Facility

Active Rx L, LS, S, CS and LSC-Band Antenna
 (1.25-1.35) GHz, P/N: 3RG1.25-1.35VV-A-XS-1; (1.35-1.45) GHz, P/N: 3RG1.35-1.45VV-A-XS-1
 (1.60-2.50) GHz, P/N: 3RG1.60-2.50VV-A-XS-1; (1.80-2.30) GHz, P/N: 3RG1.80-2.30VV-A-XS-1
 (2.00-2.30) GHz, P/N: 3RG2.00-2.30VV-A-XS-1; (2.20-2.40) GHz, P/N: 3RG2.20-2.40VV-A-XS-1
 (2.35-2.45) GHz, P/N: 3RG2.35-2.45VV-A-XS-1; (2.40-2.50) GHz, P/N: 3RG2.40-2.50VV-A-XS-1
 Other Frequency Bands, LNA, Connectors and Colors are Also Available
 Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

7		6		5		4		3		2		1																																			
										REVISIONS																																					
										ZONE	REV	DESCRIPTION	DATE	APPROVED																																	
<p style="font-size: 8px;">NOTICE OF PROPRIETARY RIGHTS THIS DOCUMENT CONTAINS CONFIDENTIAL, TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONTINGENT UPON YOUR AGREEMENT TO USE AS STATED TO USE AS STATED IN YOUR OWN DESIGN AND NOT BE REPRODUCED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF ANTCOM CORP.</p> <p style="text-align: center; font-size: 18px; font-weight: bold;">P/N: 3RG-2.35-2.45VV-A-XS-1</p>										SPECIFICATIONS																																					
										ELECTRICAL:																																					
										<table border="1" style="width:100%; border-collapse: collapse;"> <tr><td>FREQUENCY:</td><td>(X.X-X.X) GHz (See Table Below)</td></tr> <tr><td>RADIATION PATTERN:</td><td>OMNI</td></tr> <tr><td>POLARIZATION:</td><td>VERTICAL</td></tr> <tr><td>VSWR:</td><td>< 2.0:1</td></tr> <tr><td>GAIN (dB):</td><td>4.0 dBil</td></tr> <tr><td>Elevation Beam Width (3dB):</td><td>(40 to 54) °</td></tr> <tr><td>Azimuth Beam Width (3dB):</td><td>360 °</td></tr> <tr><td>IMPEDANCE:</td><td>50 Ohms</td></tr> <tr><td>LIGHTNING PROTECTION:</td><td>Yes</td></tr> </table>				FREQUENCY:	(X.X-X.X) GHz (See Table Below)	RADIATION PATTERN:	OMNI	POLARIZATION:	VERTICAL	VSWR:	< 2.0:1	GAIN (dB):	4.0 dBil	Elevation Beam Width (3dB):	(40 to 54) °	Azimuth Beam Width (3dB):	360 °	IMPEDANCE:	50 Ohms	LIGHTNING PROTECTION:	Yes																
FREQUENCY:	(X.X-X.X) GHz (See Table Below)																																														
RADIATION PATTERN:	OMNI																																														
POLARIZATION:	VERTICAL																																														
VSWR:	< 2.0:1																																														
GAIN (dB):	4.0 dBil																																														
Elevation Beam Width (3dB):	(40 to 54) °																																														
Azimuth Beam Width (3dB):	360 °																																														
IMPEDANCE:	50 Ohms																																														
LIGHTNING PROTECTION:	Yes																																														
										MECHANICAL:																																					
										<p>SIZE: BASE DIAMETER = 3.50 in.[88.90 mm], HEIGHT = 2.575 in. [65.41 mm] WEIGHT: 10.8 oz. (306 g) FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL TOP, BASE IRIDITE PER MIL-C-5441 COLOR: GLOSS WHITE #17925 PER FED-STD-595B LUSTERLESS GRAY #36320 PER FED-STD-595B OLIVE DRAB GREEN #34031 PER FED-STD-595B LUSTERLESS BLACK #37038 PER FED-STD-595B MATERIAL: 6061-T6 ALUMINUM ALLOY BASE COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT AND SKYDROL RESISTANCE, FIRE RETARDANT CONNECTOR: SMA FEMALE CONNECTOR (OPTION: TNC, SMA, N Bulkhead, MCX, MMCX, or Cable) MOUNTING: FIXED MOUNT: FROM TOP</p>																																					
										ENVIRONMENTAL:																																					
										<p>TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C] ALTITUDE: 70,000 ft. VIBRATION: > 20 G's LEAKAGE: HERMETICALLY SEALED</p>																																					
										FEDERAL & MILITARY SPECIFICATIONS:																																					
										<p>DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455</p>																																					
										<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>QTY</th> <th>DESCRIPTION</th> <th>PART NO</th> <th>FINISH</th> <th>TEST NO</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>O-RING</td> <td>2-031/N756-75, Item 550</td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>10-32 SCREW, 5/8" L</td> <td>MS24693-C273, Item 580-5/8</td> <td></td> <td>1</td> </tr> </tbody> </table>				QTY	DESCRIPTION	PART NO	FINISH	TEST NO	1	O-RING	2-031/N756-75, Item 550			4	10-32 SCREW, 5/8" L	MS24693-C273, Item 580-5/8		1																			
QTY	DESCRIPTION	PART NO	FINISH	TEST NO																																											
1	O-RING	2-031/N756-75, Item 550																																													
4	10-32 SCREW, 5/8" L	MS24693-C273, Item 580-5/8		1																																											
										<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</th> <th>ORIGINALLY DRAWN</th> <th colspan="2">ANTCOM CORP. TORRANCE, CALIFORNIA</th> </tr> </thead> <tbody> <tr> <td>FRACTIONS: TOLERANCES (DIM) ANGLES</td> <td>S. HUYNH Oct-20-10</td> <td colspan="2" rowspan="4"> <p style="text-align: center; font-size: 16px; font-weight: bold;">UHF, L, S, C (X.X-X.X) GHz 4dB OMNI ANTENNA</p> </td> </tr> <tr> <td>± 1/64 DECIMALS ± 1°</td> <td>S. HUYNH Oct-20-10</td> </tr> <tr> <td>REMOVE ALL DIMENSIONS FROM PARTS LIST</td> <td>S. HUYNH Nov-06-14</td> </tr> <tr> <td>BREAK EXTERNAL EDGES .005 TO .015 RADIUS TO .015</td> <td>P. TRAN Nov-06-14</td> </tr> <tr> <td>SCREW THREADS PER MIL-S-8879</td> <td>APPROVED S. HUYNH Nov-06-14</td> <td>REV</td> <td></td> </tr> <tr> <td>MACHINED SURFACES 12.5</td> <td></td> <td>D</td> <td>3CVE1</td> </tr> <tr> <td>DO NOT SCALE DRAWING</td> <td></td> <td>SCALE</td> <td>1/1</td> </tr> <tr> <td></td> <td></td> <td>SHEET</td> <td>1 OF 1</td> </tr> </tbody> </table>				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	ORIGINALLY DRAWN	ANTCOM CORP. TORRANCE, CALIFORNIA		FRACTIONS: TOLERANCES (DIM) ANGLES	S. HUYNH Oct-20-10	<p style="text-align: center; font-size: 16px; font-weight: bold;">UHF, L, S, C (X.X-X.X) GHz 4dB OMNI ANTENNA</p>		± 1/64 DECIMALS ± 1°	S. HUYNH Oct-20-10	REMOVE ALL DIMENSIONS FROM PARTS LIST	S. HUYNH Nov-06-14	BREAK EXTERNAL EDGES .005 TO .015 RADIUS TO .015	P. TRAN Nov-06-14	SCREW THREADS PER MIL-S-8879	APPROVED S. HUYNH Nov-06-14	REV		MACHINED SURFACES 12.5		D	3CVE1	DO NOT SCALE DRAWING		SCALE	1/1			SHEET	1 OF 1				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	ORIGINALLY DRAWN	ANTCOM CORP. TORRANCE, CALIFORNIA																																													
FRACTIONS: TOLERANCES (DIM) ANGLES	S. HUYNH Oct-20-10	<p style="text-align: center; font-size: 16px; font-weight: bold;">UHF, L, S, C (X.X-X.X) GHz 4dB OMNI ANTENNA</p>																																													
± 1/64 DECIMALS ± 1°	S. HUYNH Oct-20-10																																														
REMOVE ALL DIMENSIONS FROM PARTS LIST	S. HUYNH Nov-06-14																																														
BREAK EXTERNAL EDGES .005 TO .015 RADIUS TO .015	P. TRAN Nov-06-14																																														
SCREW THREADS PER MIL-S-8879	APPROVED S. HUYNH Nov-06-14	REV																																													
MACHINED SURFACES 12.5		D	3CVE1																																												
DO NOT SCALE DRAWING		SCALE	1/1																																												
		SHEET	1 OF 1																																												

NMO Connector Option is Now Available for Some Antennas