



UHF, L, S, C, X, or Ku-Band Antennas, P/N: 52-X.XX-X.XXX-MX-X:
3.5"/2.6" Diameter x 4.5" Tall, 1"-14 Pipe/Magnetic Mount Antenna Configurations
LNA Options are Available



ISO 9001:2008/FAA Approved Facility Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

6	5	4	3	1																																																																																						
<p>NOTICE OF PROPRIETARY RIGHTS THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONDITIONED UPON YOUR ASSENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY (AND DOES NOT INCLUDE MANUFACTURE OR PROCESSING USES). ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM, CORP.</p>			<p>SPECIFICATIONS</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">REVISIONS</th> <th>DATE</th> <th>APPROVED</th> </tr> <tr> <th>ZONE</th> <th>REV</th> <th>DESCRIPTION</th> <th></th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>		REVISIONS		DATE	APPROVED	ZONE	REV	DESCRIPTION																																																																															
REVISIONS		DATE	APPROVED																																																																																							
ZONE	REV	DESCRIPTION																																																																																								
<p>ELECTRICAL:</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>UHF</th> <th>L-BAND</th> <th>L/S-BAND</th> <th>S-BAND</th> <th>C-BAND</th> </tr> </thead> <tbody> <tr> <td>FREQUENCY (MHz):</td> <td>(350-400) (400-450) (810-960)</td> <td>(1332-1540)</td> <td>(1610-1850)</td> <td>(1610-2500)</td> <td>(2400-2500) (4400-5850)</td> </tr> <tr> <td>PATTERN:</td> <td colspan="5">OMNIDIRECTIONAL</td> </tr> <tr> <td>POLARIZATION:</td> <td colspan="5">VERTICAL</td> </tr> <tr> <td>ANTENNA GAIN :</td> <td colspan="5">> 2 dB</td> </tr> <tr> <td>VSWR:</td> <td colspan="5">2.0:1</td> </tr> <tr> <td>OUTPUT IMPEDANCE:</td> <td colspan="5">50 Ω</td> </tr> <tr> <td>POWER HANDLING:</td> <td colspan="5">>50 watts (Without LNA)</td> </tr> <tr> <td>LNA OPTION:</td> <td colspan="5">GAIN: 20 dB, NF: 4.1 dB, OP1dB: +18dB, OIP3: +33dB DC: (5 to 24) Volt @ <70mA</td> </tr> </tbody> </table>				UHF	L-BAND	L/S-BAND	S-BAND	C-BAND	FREQUENCY (MHz):	(350-400) (400-450) (810-960)	(1332-1540)	(1610-1850)	(1610-2500)	(2400-2500) (4400-5850)	PATTERN:	OMNIDIRECTIONAL					POLARIZATION:	VERTICAL					ANTENNA GAIN :	> 2 dB					VSWR:	2.0:1					OUTPUT IMPEDANCE:	50 Ω					POWER HANDLING:	>50 watts (Without LNA)					LNA OPTION:	GAIN: 20 dB, NF: 4.1 dB, OP1dB: +18dB, OIP3: +33dB DC: (5 to 24) Volt @ <70mA					<p>MECHANICAL:</p> <p>SIZE: DIAMETER = 2.653 in. [67.38 mm] HEIGHT = 4.618 in. [117.29 mm] 4.5 in [35.5mm] (L/UHF Band), See Part Number Below</p> <p>WEIGHT: 5.15 oz. (146 g)</p> <p>FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL BASE IRIDITE PER MIL-C-5441</p> <p>COLOR: LUSTERLESS GRAY #36320 PER FED-STD-595B GLOSS WHITE #17925 PER FED-STD-595B OLIVE DRAB GREEN #34031 PER FED-STD-595B LUSTERLESS BLACK #37038 PER FED-STD-595B</p> <p>MATERIAL: 6061-T6 ALUMINUM ALLOY BASE THERMOSET PLASTIC RADOME, UV, ABRASION AND SKYDROL RESISTANCE</p> <p>CONNECTOR: SMA FEMALE (TNC, N, AND OTHERS ARE OPTIONAL)</p> <p>ENVIRONMENTAL:</p> <p>TEMPERATURE: -67°F TO +185°F [-55°C TO +85°C] ALTITUDE: 70,000 ft. VIBRATION: >10 G's LEAKAGE: HERMETICALLY SEALED</p> <p>FEDERAL & MILITARY SPECIFICATIONS:</p> <p>DESIGN TO: DO-160D, MIL-C-5541, MIL-E-5400, MIL-I-45208A, AND MIL-STD-810E</p>																																	
	UHF	L-BAND	L/S-BAND	S-BAND	C-BAND																																																																																					
FREQUENCY (MHz):	(350-400) (400-450) (810-960)	(1332-1540)	(1610-1850)	(1610-2500)	(2400-2500) (4400-5850)																																																																																					
PATTERN:	OMNIDIRECTIONAL																																																																																									
POLARIZATION:	VERTICAL																																																																																									
ANTENNA GAIN :	> 2 dB																																																																																									
VSWR:	2.0:1																																																																																									
OUTPUT IMPEDANCE:	50 Ω																																																																																									
POWER HANDLING:	>50 watts (Without LNA)																																																																																									
LNA OPTION:	GAIN: 20 dB, NF: 4.1 dB, OP1dB: +18dB, OIP3: +33dB DC: (5 to 24) Volt @ <70mA																																																																																									
<p>Optional Top Mounting: 4x10-32 Screws 4X Ø.20 [Ø5.11] Thru. ✓ Ø.385 [Ø9.78] X 100"</p> <p>REMOVABLE MAGNETIC MOUNT</p> <p>SMA CONNECTOR (OPTION: TNC, N, N Bulkhead MCX, MMCX, or Cable)</p> <p>NAMEPLATE</p>																																																																																										
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>CONFIGURATION:</th> <th>FREQUENCY:</th> <th>LNA:</th> <th>CABLE'S LENGTH:</th> <th>CONNECTOR:</th> <th>COLOR:</th> </tr> </thead> <tbody> <tr> <td>52: 2.6inDiameterBase</td> <td>0.31-0.40: (310-400) MHz</td> <td>A: WITH +20 dB LNA</td> <td>X: NO CABLE</td> <td>S: SMA; RS: R-SMA; Q: OMA</td> <td>-1: GLOSS WHITE #17925 PER FED-STD-595B</td> </tr> <tr> <td></td> <td>0.35-0.40: (350-400) MHz</td> <td>P: WITHOUT LNA</td> <td>M: WITH MAG. MOUNT</td> <td>M: MCX; MM: MMCX</td> <td>-2: LUSTERLESS GRAY #36320 PER FED-STD-595B</td> </tr> <tr> <td></td> <td>0.40-0.45: (400-450) MHz</td> <td></td> <td>#: CABLE LENGTH (IN)</td> <td>N: N; NB: N Bulkhead</td> <td>-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B</td> </tr> <tr> <td></td> <td>0.81-0.96: (810-960) MHz</td> <td></td> <td>R: RIGHT ANGLE CON.</td> <td>T: TNC; TB: TNC- Bulkhead</td> <td>-4: LUSTERLESS BLACK #37038 PER FED-STD-595B</td> </tr> <tr> <td></td> <td>0.85-1.90: (850-1900) MHz</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>1.33-1.54: (1332-1540) MHz</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>1.61-1.85: (1610-1850) MHz</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>1.61-2.50: (1610-2500) MHz</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>2.40-2.50: (2400-2500) MHz</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>4.40-5.85: (4400-5850) MHz</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>X.XX - Y.YY: (X.XX - Y.YY) GHz</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>			CONFIGURATION:	FREQUENCY:	LNA:	CABLE'S LENGTH:	CONNECTOR:	COLOR:	52: 2.6inDiameterBase	0.31-0.40: (310-400) MHz	A: WITH +20 dB LNA	X: NO CABLE	S: SMA; RS: R-SMA; Q: OMA	-1: GLOSS WHITE #17925 PER FED-STD-595B		0.35-0.40: (350-400) MHz	P: WITHOUT LNA	M: WITH MAG. MOUNT	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B		0.40-0.45: (400-450) MHz		#: CABLE LENGTH (IN)	N: N; NB: N Bulkhead	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B		0.81-0.96: (810-960) MHz		R: RIGHT ANGLE CON.	T: TNC; TB: TNC- Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B		0.85-1.90: (850-1900) MHz						1.33-1.54: (1332-1540) MHz						1.61-1.85: (1610-1850) MHz						1.61-2.50: (1610-2500) MHz						2.40-2.50: (2400-2500) MHz						4.40-5.85: (4400-5850) MHz						X.XX - Y.YY: (X.XX - Y.YY) GHz					<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>1</th> <th>DESCRIPTION</th> <th>PART NO</th> <th>SPECIFICATION</th> <th>MATERIAL</th> <th>FINISH</th> <th>ITEM NO</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table> <p>QUANTITY RECD</p> <p>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRACTIONS TOLERANCES ARE ANGLES ± 1/64 .XX ± .015 .XXX ± .005 ± 1°</p> <p>TOLERANCE SYM PER ANSI Y14.5</p> <p>REMOVE ALL BURRS BREAK EXTERNAL EDGES .005 TO .015 FILLETS R .005 TO R .030 SCREW THREADS PER MIL-S-8879 DIA'S ON A COMMON & Z .005 MACHINED SURFACES .25/</p> <p>DO NOT SCALE DRAWING</p>		1	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	ITEM NO							
CONFIGURATION:	FREQUENCY:	LNA:	CABLE'S LENGTH:	CONNECTOR:	COLOR:																																																																																					
52: 2.6inDiameterBase	0.31-0.40: (310-400) MHz	A: WITH +20 dB LNA	X: NO CABLE	S: SMA; RS: R-SMA; Q: OMA	-1: GLOSS WHITE #17925 PER FED-STD-595B																																																																																					
	0.35-0.40: (350-400) MHz	P: WITHOUT LNA	M: WITH MAG. MOUNT	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B																																																																																					
	0.40-0.45: (400-450) MHz		#: CABLE LENGTH (IN)	N: N; NB: N Bulkhead	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B																																																																																					
	0.81-0.96: (810-960) MHz		R: RIGHT ANGLE CON.	T: TNC; TB: TNC- Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B																																																																																					
	0.85-1.90: (850-1900) MHz																																																																																									
	1.33-1.54: (1332-1540) MHz																																																																																									
	1.61-1.85: (1610-1850) MHz																																																																																									
	1.61-2.50: (1610-2500) MHz																																																																																									
	2.40-2.50: (2400-2500) MHz																																																																																									
	4.40-5.85: (4400-5850) MHz																																																																																									
	X.XX - Y.YY: (X.XX - Y.YY) GHz																																																																																									
1	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	ITEM NO																																																																																				
<p align="center">P/N: 52-0.40-0.45P-MS-4</p>			<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">ANTCOM CORP. TORRANCE CALIFORNIA</td> </tr> <tr> <td colspan="2" style="text-align: center;">UHF, L, L/S, S, or C-BAND ACTIVE or PASSIVE OMNI ANTENNA</td> </tr> <tr> <td> DRAWN: CHECKED: ENGINEER: APPROVED: S. HUYNH April-05-05 </td> <td> SIZE: CASE NO: D 3CVE1 </td> </tr> <tr> <td> DO NOT SCALE DRAWING </td> <td> DRAWING NO: 52-X.XX-X.XXX-MX-X SCALE 1/1 SHEET 1 OF 1 </td> </tr> </table>		ANTCOM CORP. TORRANCE CALIFORNIA		UHF, L, L/S, S, or C-BAND ACTIVE or PASSIVE OMNI ANTENNA		DRAWN: CHECKED: ENGINEER: APPROVED: S. HUYNH April-05-05	SIZE: CASE NO: D 3CVE1	DO NOT SCALE DRAWING	DRAWING NO: 52-X.XX-X.XXX-MX-X SCALE 1/1 SHEET 1 OF 1																																																																														
ANTCOM CORP. TORRANCE CALIFORNIA																																																																																										
UHF, L, L/S, S, or C-BAND ACTIVE or PASSIVE OMNI ANTENNA																																																																																										
DRAWN: CHECKED: ENGINEER: APPROVED: S. HUYNH April-05-05	SIZE: CASE NO: D 3CVE1																																																																																									
DO NOT SCALE DRAWING	DRAWING NO: 52-X.XX-X.XXX-MX-X SCALE 1/1 SHEET 1 OF 1																																																																																									

NMO Connector Option is Now Available for Some Antennas