




ISO 9001:2008/FAA Approved Facility

GPS/GSM(ISM)-Band Antenna
 P/N: 5G0915RL-PA-XSS-UU (L1 GPS/ISM, SMA Connector)
 P/N: 5G091215RL-PA-XSS-UU (L1/L2 GPS/ISM, SMA Connector)
 P/N: 5G09G5RL-PA-XSS-UU (L1/L2 GPS/Glonass/ISM, SMA Connector)
 Other Frequencies and Connectors are Also Available
 Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>



FAA Approved
TSO Antennas



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

NOTICE OF PROPRIETARY RIGHTS
THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO ANY OTHER PERSON OR ENTITY WITHOUT THE WRITTEN CONSENT OF ANTCOM CORP. IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

NOTES: UNLESS OTHERWISE SPECIFIED:
 1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]
 2. ALL SCREWS ARE SUPPLIED BY ANTCOM CORPORATION

P/N: 5G0915RL-PA-XSS-UU

SPECIFICATIONS

ELECTRICAL:

	GPS (L1 or L1/L2, See P/N in Bottom Table)		GSM(ISM)	
	L1: (1575.4 ±13)		L2: (1227.6 ±13) MHz	
FREQUENCY:			(See Bottom Table)	
RADIATION PATTERN:	HEMISPHERICAL			
POLARIZATION:	RHCP			
VSWR:	< 1.5:1			
GAIN (dB):	F.S.	4 ft.G.P	F.S.	4 ft.G.P
@ 90° (Zenith):	+ 4.6	+ 2.9	+ 1.8	+ 5.3
@ 10° Elevation:	- 2.5	- 1.8	- 4.2	- 2.3
@ 20° Elevation:	- 1.1	+ 0.7	- 2.9	+ 0.4
@ 30° Elevation:	+ 0.5	+ 1.7	- 2.0	+ 2.3
@ 60° to 90° Elevation:	> 3.6	> 2.1	> 0.9	> 3.2
BEAM WIDTH (3dB):	103°	146°	108°	74°
AXIAL RATIO @ Zenith:	2 dB			
POWER HANDLING:	1 Watt			
LIGHTNING PROTECTION:	DC GROUNDING			
FILTER:	2 2-POL			
LNA GAIN:	(33.0±1.0) dB			
LNA P 1dB Out:	+16 dBm			
LNA NOISE FIGURE:	2.9 dB (Filter loss is Included)			
VOLTAGE/CURRENT:	(+2.8 TO +28) Volts DC / (30 TO 50) mA			

MECHANICAL:

SIZE: WIDTH: 2.20 in. [55.88 mm], LENGTH: 5.026 in. [127.66 mm]
 HEIGHT: 0.764 in. [19.41 mm]
 WEIGHT: < 8.0 oz. (226 g)
 FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL
 BASE IRIDITE PER MIL-C-5441

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE
 COMPOSITE RADOME, IMPACT, ABRASION,
 UV, SOLVENT, AND SKYDROL RESISTANCE,
 FIRE RETARDANT

CONNECTOR: GPS: TNC-F (Blue), IRIDIUM: TNC-F (Red), XM: TNC-F (Green)
 (OPTION: SMA, TNC, TNC Bulkhead, N, N Bulkhead,
 BNC, MCX, MMCX, or Cable)

MOUNTING: FLAT FIXED MOUNT: O-RING &
 4 x 10-32 MOUNTING SCREWS PROVIDED

ENVIRONMENTAL:

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]
 ALTITUDE: 70,000 ft.
 VIBRATION: > 30 G's
 LEAKAGE: HERMETICALLY SEALED

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541,
 MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

ZONE	REV	DESCRIPTION	DATE	APPROVED
4		PANHEAD SCREW, 10-32, 1" (Item 579)		MS24693C276
1		O-RING, Item 552		2-038-N756-75

QUANTITY	RECD	DESCRIPTION	PARTS LIST	PART NO	FINISH	ITEM
						NO

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES
 FRACTIONS TO THIRDS ANGLES
 DECIMALS TO TWO
 ± 1/64 .002 .015

ORIGINAL DESIGNED S. HUYNH July-12-09
 ORIGINAL DESIGNED S. HUYNH July-12-09
 UPDATED S. HUYNH Feb-19-14
 UPDATE DRAWN P. TRAN Feb-19-14
 APPROVED S. HUYNH Feb-19-14

ANTCOM CORP. TORRANCE CALIFORNIA
 FLAT FIXED MOUNT
 GSM(ISM)/GPS
 ANTENNA

SCALE 1/1 SHEET 1 OF 1

NMO Connector Option is Now Available for Some Antennas