



Active L1 GPS/IRIDIUM/WI-FI Antenna, P/N: 5G151624RRL-A2P-XTTT-X (20dB, TNC Connectors)  
 Active L1/L2 GPS/IRIDIUM/WI-FI Antenna, P/N: S5GIR121625RRL-APP-XSSX-X (33dB, SMA Connectors)  
 Active L1/L2 GPS/IRIDIUM/WI-FI Antenna, P/N: S5GIR121625RRL-APP-XSSX-UU  
 (33dB, SMA, "-UU" (Gray) for Under Water Applications (10,000meter))



FAA Approved  
TSO Antennas

ISO 9001:2008/FAA Approved Facility

Antenna Mounts: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501 . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: [antennas@antcom.com](mailto:antennas@antcom.com) . <http://www.antcom.com>

**NOTICE OF PROPRIETARY RIGHTS:**  
 THIS DOCUMENT CONTAINS CONFIDENTIAL, TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY CONSIDERED UNLAWFUL UNLESS YOUR USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY (AND DOES NOT INCLUDE MANUFACTURE OR PROCESSING). ANY OTHER USE IS EXPRESSLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

**SPECIFICATIONS**

**ELECTRICAL:**

	L1 GPS/L-Band	IRIDIUM	WIFI
FREQUENCY:	(1575.42 ±12) MHz,	(1610.0 - 1626.5) MHz	(2400-2500) MHz
RADIATION PATTERN:	(1555.00 ±17) MHz	HEMISPHERICAL	VERTICAL
POLARIZATION:	RHCP	RHCP	LHCP
VSWR:	< 1.5:1	< 1.5:1	< 2:1
GAIN (dB):	F.S	4 ft G.P.	F.S
@ 90° (Zenith):	+ 4.6	+ 2.9	+4.9
@ 10° Elevation (Ave):	- 2.5	- 1.8	-2.4
@ 20° Elevation (Ave):	- 1.1	+ 0.7	-0.8
@ 30° Elevation (Ave):	+ 0.5	+ 1.7	+0.8
@ 45° Elevation (Ave):	> 3.6	> 2.1	+2.8
@ 70° Elevation (Ave):	> 3.6	> 2.1	+4.6
AXIAL RATIO @ Zenith:	2 dB	2 dB	
POWER HANDLING:	1 Watt		
DC GROUNDING:	YES (LIGHTNING PROTECTION)		
FILTER (REJ. @1616 MHz):			
REJECTION @ (-50/+50) MHz:	-45 dB / -40 dB		
@ (-100/+100) MHz:	< -65 dB		
LNA GAIN:	22 dB (P1dBout = +13 dBm)		
LNA NOISE FIGURE:	2.2 dB		
LNA VOLTAGE:	(+2.5 to +24) Volts DC FROM Rx RF CON.		
LNA DRAWING CURRENT:	< 30 mA		

**MECHANICAL:**

SIZE: WIDTH: 2.20 in. [55.88 mm], LENGTH: 5.026 in [127.66 mm], HEIGHT: 0.721 in. [18.31 mm]  
 WEIGHT: < 8.0 oz. (226 g)  
 FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL BASE IRIDITE PER MIL-C-5441  
 MATERIAL: 6061-T6 ALUMINUM ALLOY BASE COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT AND SKYDROL RESISTANCE, FIRE RETARDANT  
 CONNECTOR: GPS: TNC-F (Blue), IRIDIUM: TNC-F (Red), WIFI: TNC-F (Green) (OPTION: SMA, TNC, TNC Bulkhead, N, N Bulkhead, MCX, MMCX, or Cable)  
 MOUNTING: FLAT FIXED MOUNT; O-RING & 4 x 10-32 MOUNTING SCREWS PROVIDED

**ENVIRONMENTAL:**

TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]  
 ALTITUDE: 70,000 ft.  
 VIBRATION: > 30 G's  
 LEAKAGE: HERMETICALLY SEALED

**FEDERAL & MILITARY SPECIFICATIONS:**

FAA TSO-C144, DO-160D, DO-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

**DESIGN & CONSTRUCTION:**

QUANTITY	DESCRIPTION	PART NO	MATERIAL	FINISH	HOW SUPPLIED
4	MOUNTING SCREW: (10-32, 1")	MS24693C276	-	-	5
1	O-RING	2-038-N756-75	-	-	3

**CONFIGURATION**

FRONT BAND:	GPS/XM LNA:	CABLE'S LENGTH:	GPS/IRIDIUM/XM CON:	COLOR:
1: 2" SQ. (FLAT)	R: GPS/IRIDIUM	X: NO CABLE	S: SMA; P: PINS	-1: GLOSS WHITE #17925 PER FED-STD-595B
1.9: 1.9" SQ. (FLAT)	L: WIFI	M: WITH MAG. MOUNT	M: MCX; MM: MMCX	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
2: 2.6" DIA. (FLAT)	A2: WITH LNA	#: CABLE LENGTH (IN)	N: N; NB: N-Bulkhead	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
3: 3.5" DIA. (FLAT)	P: WITHOUT LNA	R: RIGHT ANGLE CON.	T: TNC; TB: TNC- Bulkhead	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B
4: MINI ARINC (FLAT)	A: 33dB			
5G: (5.0x2.2)in Rect.				
5B: (HELIX BLADE)				
5D: (HELIX HANDHELD)				

**NOTES:** UNLESS OTHERWISE SPECIFIED:  
 1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]  
 2. ALL SCREWS ARE SUPPLIED BY ANTCOM CORPORATION

**ANTCOM CORP.** TORRANCE, CALIFORNIA  
**FLAT FIXED MOUNT**  
**GPS/IRIDIUM/WIFI**  
**ANTENNA**

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES  
 TOLERANCE SURF PER ANSI Y14.6  
 ± 1/64 SURF SCHEM ANGLES ± 1°  
 REMOVE ALL BURRS  
 BREAK EXTERNAL EDGES .005 TO .015  
 FILE IF .002 TO .010  
 50% IF THERE IS .010 TO .020  
 DAYS ON A COMMON & 27.000  
 MACHINED SURFACES  
 DO NOT SCALE DRAWING

APPROVED: S. HUYNH  
 Mor-08-12

SCALE 1/1

SHEET 1 OF 1

NMO Connector Option is Now Available for Some Antennas

**P/N: 5G151624RRL-A2P-XTTT-1**