



High Temperature Performance L, S, C, X, or Ku-Band Antennas for Telemetry/Data Link Applications, P/N: 6BH-X.XX-X.XXV-XS-X-HF3 1" Tall Blade Configuration, Also Available in UHF and Other Frequencies Bands



ISO 9001:2008/FAA Approved Facility

Antenna Mounts/Adapters: <http://www.antcom.com/documents/catalogs/PeripheralAntennaProducts2.pdf>

ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . <http://www.antcom.com>

7
6
5
4
3
2
1

NOTICE OF PROPRIETARY RIGHTS
THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO YOU IS EXPRESSLY FORBIDDEN UNLESS YOU AGREE THAT YOU WILL BE LIMITED TO USE WITHIN YOUR COMPANY ONLY (YOU WILL NOT INCLUDE, MANUFACTURE OR PRODUCE UNLESS ANY OTHER USE IS EXPRESSLY FORBIDDEN) WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

SPECIFICATIONS

ZONE		REV	DESCRIPTION	DATE	APPROVED
-		-	-	-	-

REVISIONS	
DATE	APPROVED
-	-

A
B
C
D

7
6
5
4
3
2
1

P/N: 6BH-X.XX-X.XXV-XS-X-HF3

ELECTRICAL:

FREQUENCY	PART # for SMA CON.	PART # for TNC CON.
1.43-1.54 GHz	6BH-1.43-1.54V-XS-X	6BH-1.43-1.54V-XT-X
1.71-1.85 GHz	6BH-1.71-1.85V-XS-X	6BH-1.71-1.85V-XT-X
1.70-2.70 GHz	6BH-1.70-2.70V-XS-X	6BH-1.70-2.70V-XT-X
2.20-2.29 GHz	6BH-2.20-2.29V-XS-X	6BH-2.20-2.29V-XT-X
4.00-6.00 GHz	6BH-4.00-6.00V-XS-X	
4.50-5.00 GHz	6BH-4.50-5.00V-XS-X	
5.40-5.90 GHz	6BH-5.40-5.90V-XS-X	
6.00-8.00 GHz	6BH-6.00-8.00V-XS-X	
8.90-9.50 GHz	6BH-8.90-9.50V-XS-X	
14.5-15.5 GHz	6BH-14.5-15.5V-XS-X	

RADIATION PATTERN:	OMNIDIRECTIONAL
POLARIZATION:	VERTICAL
ANTENNA GAIN:	(2 to 5) dB
VSWR:	< 2.0:1
OUTPUT IMPEDANCE:	50 Ω
POWER HANDLING:	300 Watts
DC GROUNDING:	YES (LIGHTNING PROTECTION)

MECHANICAL:

SIZE: WIDTH 0.45 in. [11.43 mm], LENGTH 2.50 in. [63.50 mm], HEIGHT 0.90 in. [22.99 mm]

WEIGHT: 0.95 oz. (26.9 g)

FINISH: YELLOW IRITE PER MIL-C-5541F, TYPE 1 CLASS 1A

COLOR: LUSTERLESS GRAY #36320 PER FED-STD-595B
GLOSS WHITE #17925 PER FED-STD-595B
OLIVE DRAB GREEN #34031 PER FED-STD-595B
LUSTERLESS BLACK #37038 PER FED-STD-595B

MATERIAL: 6061-T6 ALUMINUM ALLOY BASE

CONNECTOR: TNC FEMALE
(OPTIONAL: SMA FEMALE CONNECTOR)

ENVIRONMENTAL:

TEMPERATURE: -85°F TO +1,100°F [-65°C TO +600°C]

ALTITUDE: 70,000 ft.

VIBRATION: >30 G's

FEDERAL & MILITARY SPECIFICATIONS:

DESIGN TO: FAA TSO-C144, DO-160D, DO-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

2. MOUNTING SCREWS ARE SUPPLIED BY ANTCOM CORPORATION

1. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS [mm]

NOTES: UNLESS OTHERWISE SPECIFIED:

QTY	DESCRIPTION	PART NO	SPECIFICATION	MATERIAL	FINISH	TEST NO
2	SCREW, MOUNTING	MS24693C274	-	-	-	1
-2	-1	-	-	-	-	-

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRACTIONS DECIMALS ANGLES ± 1/64 .001 .015 .002 90° ± 1°

TOLERANCE SURF PER ANSI Y14.6

RELIEVE ALL SHARP BREAK EXTERNAL EDGES .005 TO .015 FILED & .005 TO .010 SCREW THREADS PER MIL-S-8879 DATE ON A DIMENSION SURF MACHINED SURFACES

DO NOT SCALE DRAWING

7
6
5
4
3
2
1

NMO Connector Option is Now Available for Some Antennas