



ISO 9001:2008/FAA Approved Facility

New High Gain Array Antenna

P/N: 9X9A-TL-P-XT-1 (Thuraya); P/N: 9X9A-INR-P-XT-1 (Inmarsat/Iridium)
 P/N: 9X9A-1.6-1.9V-P-XT-1 (1.6 - 1.9 GHz); P/N: 9X9A-2.2-2.3V-P-XT-1 (2.2 - 2.3 GHz)
 P/N: 9X9A-2.2-2.4V-P-XT-1 (2.2 - 2.4 GHz); P/N: 9X9A-2.2-2.5V-P-XT-1 (2.2 - 2.5 GHz)
 P/N: 9X9A-2.4-2.5V-P-XT-1 (2.4 - 2.5 GHz); P/N: 9X9A-LSV-P-XT-1 ((1.625 - 1.85)/(2.2 - 2.4) GHz)



ANTCOM CORPORATION . 367 Van Ness Way, Suite 602 . Torrance, CA 90501, USA . Tel: (310) 782-1076 . Fax: (310) 782-1086 . E-mail: antennas@antcom.com . http://www.antcom.com

NOTICE OF PROPRIETARY RIGHTS
 THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA INCLUDING TRADE SECRETS PROPRIETARY TO ANTCOM CORP. DISCLOSURE OF THIS DATA TO ANY OTHER PARTY WITHOUT WRITTEN PERMISSION FROM ANTCOM CORP. IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN CONSENT OF ANTCOM CORP.

9X9A-X.X-Y.YV-P-XT-5

FREQUENCY BAND:	S/C-BAND POL.	LNA:	CONNECTOR:	COLOR:
T: Rx/Tx Thuraya	V: VERTICAL	A: ACTIVE	S: SMA	-1: GLOSS WHITE #17925 PER FED-STD-595B
IN: Rx/Tx Inmarsat/Iridium	R: RHCP	P: PASSIVE	Q: QMA	-2: LUSTERLESS GRAY #36320 PER FED-STD-595B
1.6-1.9: (1.6 - 1.9) GHz	L: LHVP		SMB: SMB	-3: OLIVE DRAB GREEN #34031 PER FED-STD-595B
2.2-2.3: (2.2 - 2.3) GHz			T: TNC	-4: LUSTERLESS BLACK #37038 PER FED-STD-595B
2.2-2.4: (2.2 - 2.4) GHz			N: N	-5: TAN #33446 PER FED-STD-595B
2.4-2.5: (2.4 - 2.5) GHz				
2.2-2.5: (2.2 - 2.5) GHz				
LS: (1.625 - 1.85)/(2.2 - 2.4) GHz				
X.X-Y.Y: (X.XX - Y.YY) GHz				

SPECIFICATIONS

ELECTRICAL:
 FREQUENCY: (X.XX - X.XX) GHz - See Below Table for P/N
 PATTERN: DIRECTIONAL
 POLARIZATION: RHCP, LHCP, or LINEAR - See Below Table for P/N
 ANTENNA GAIN: 12 dB
 BEAM WIDTH (deg): 48 Deg.
 VSWR: 2.0:1
 OUTPUT IMPEDANCE: 50 ohms
 POWER HANDLING: 100 watts
 DC GROUNDING: YES

LNA OPTION (For Rx Only):
 LNA GAIN: 33 dB (P1dBout = +13 dBm)
 LNA NOISE FIGURE: 2.2 dB
 LNA VOLTAGE: (+2.5 to +24) Volts DC
 LNA DRAWING CURRENT: < 30 mA

MECHANICAL:
 SIZE: 9.39 In x 9.39 In x 0.56 In
 WEIGHT: 10.8 oz. (306 g)
 FINISH: SKYDROL RESISTANT POLYURETHANE ENAMEL, AND BLACK ANODIZED
 MATERIAL: 6061-T6 ALUMINUM ALLOY BASE COMPOSITE RADOME, IMPACT, ABRASION, UV, SOLVENT, AND SKYDROL RESISTANCE, FIRE RETARDANT
 CONNECTOR: TNC FEMALE (OPTION: SMA, QMA, SMB, N)

ENVIRONMENTAL:
 TEMPERATURE: -67 °F TO +185 °F [-55 °C TO +85 °C]
 ALTITUDE: 30,000 ft.
 VIBRATION: > 20 G's
 LEAKAGE: HERMETICALLY SEALED

FEDERAL & MILITARY SPECIFICATIONS:
DESIGN TO: FAA TSO-C144, DO-160D, D0-228, MIL-C-5541, MIL-E-5400, MIL-I-45208A, MIL-STD-810, AND SAE J1455

ZONE	REV	DESCRIPTION	DATE	APPROVED
1				
2				
3				